

RENOVA TRACTION: SPECIFICATIONS

Load/Capacity		Car			Lift Shaft									
Persons	Q Load	AC Width	FC Depth	PL Clear Opening	Entrance		Side-opening Doors		Centre-opening Doors**		HF Pit	HUP Headroom		
					Accessibility	No. of Entrances	AH ¹ Width	FH ² Depth	AH Width	FH ³ Depth				
4 pers	320kg	825	1100	700		1	1400	1500			280	2800		
						2x 180°	1400	1610						
						2x 90°	1570	1500					605	
6pers	450kg	1000	1250	800		1	1575	1650			280		2800	
						2x 180°	1575	1760						
						2x 90°	1750	1650						605
8 pers	630kg	1100	1400	900		1	1675	1775			280			2800
						2x 180°	1675	1960						
						2x 90° *	1870	1775						
	1200	1250	900			1	1775	1700			280			
						2x 180°	1775	1810						
						2x 90° *	1970	1700				605		

* No granite floor

** Centre Opening Doors are available upon request

VISIT OUR SHOWROOMS

NSW
64 Penshurst St
Willoughby NSW 2068
T. 02. 8116 1500
F. 02. 8116 1511

VIC - SA - TAS
7 Hoddle St
Collingwood VIC 3066
T. 03. 9094 8600
F. 03. 9094 8611

QLD
17 Campbell St
Bowen Hills QLD 4006
T. 07. 3851 7500
F. 07. 3851 7511

WA
23 Plaistowe Mews
West Perth WA 6005
T. 08. 9322 4688
F. 08. 9322 4655